

## MODEL TL-DR-55 ATEX

# Single Stage Drum Washer

RotaJet batch drum washing machines are made to be used with low flash point flammable solvent. Dirty open-top 55 gallon drums are loaded into the machine, the door is closed and cycle started.

The cleaning process is fully automated, and the drums are washed, and ready for production in a matter of minutes. Systems are perfect for paint, ink and printing companies.

### Features Include:

- automatic wash cycle
- high volume vapor extraction system protects operator prior to door opening
- solvent spray pressure at 4-6 Bar, 87 PSI max
- short cycle times - 10 to 12 minutes typical
- easy integration into full-scale solvent recovery systems
- designed for ANSI MH2-2004 55 gallon openhead drums
- ATEX certified
- rated Class 1, Division 1, Group D



BACK SIDE

### TECHNICAL OVERVIEW

Max Load	220 lbs
Max Component Height	35.4 in
Wash Sump Capacity	60.75 gal
Material of Construction	6 gauge mild steel
Pump Size	(1) 1.5" air diaphragm
Bottom Spray Bar Drive Detail	Fluid
Air Inlet Pressure	87 PSI Max
Pump Air Consumption	15 cfm
Loading Height	34.4 in
Max Internal Pump Pressure	65 PSI
Cycle Time	approx. 12 min

## MODEL TL-DR-55 ATEX

# Single Stage Drum Washer

### OVERALL SIZE

Length	43.3 in
Width	45.24 in
Height (door closed)	59 in
Height (door open)	86.6 in

### COMPONENTS

A	Clean Out Door
B	Control Panel
C	Machine Body
D	Machine Cover Lift Support
E	Machine Cover
F	Filter Baskets (3)
G	200 Liter Support Frame
H	Spray Nozzle
I	Wash Pump
J	Air Inlet
K	4" Extraction Damper
L	Air Extraction Unit
M	Drain Valve
N	Control Panel

